NE8FFX6-W

Coupleur Etanche Ethercon catégorie 6a pour rallonger les câbles







All rights reserved / 04.11.2026

NEUTRIK

Caractéristiques & Avantages

- Coupleur renforcé avec conformité des composants CAT6A selon ISO / CEI 11801 et TIA / EIA 568-C.2
- IP65 protégé lorsqu'il est couplé avec NE8MX6 *
- Compatible avec la prise RJ45 standard
- Forme révolutionnaire métal recouvert de caoutchouc
- L'adaptateur offre un système de verrouillage robuste et testé des millions de fois

Technical Information

Product	
Title	NE8FFX6-W
Connection Type	Adapter
Gender	female

Electrical	
Contact resistance	< 200 mΩ
Dielectric strength	> 1.5 kVdc
Insulation resistance	> 0.5 GΩ
Rated current per contact	1.5 A
Transmission performance	CAT6A, acc. TIA/EIA rating Class EA, acc. IEC/ISO/EN rating
Power over Ethernet	PoE+ acc. IEEE 802.3at

All rights reserved / 04.11.2026

NEUTRIK

Mechanical	
Insertion force	≤ 50 N
Withdrawal force	≤ 50 N
Lifetime	> 1000 mating cycles
Wiring	Feedthrough
Locking device	Latch lock

Material	
Contact plating	Au
Shell	Rubber (EPDM)
Strain relief	CuZn35Pb2, Tin plated

Environmental	
Temperature range	- 30 °C to + 80 °C
Protection class	IP65 (in combination with NE8MX*)

All rights reserved / 04.11.2026